

Data Sheet Flat Signs

Product description

Application

The signs are hardy, steel based with an edge of protective plastic. Included with the signs are coding in magnetic letters/numbers, Coding can be placed on one or both sides of the sign. The default contains 2 holes for adequate and efficient mounting. This product is used for identification of aisles, racks, sections, load and unload stations, etc.



Dimensions

Default dimensions and max. code length:

Sign Dimension	Max. no. of positions	Character height	Reading distance	Weight
200 x 200 mm	2 / 3	150 mm / 100mm	30 m / 20 m	0.40 kg
200 x 450 mm	5	150 mm	30 m	0.85 kg
300 x 300 mm	2 / 3	200 mm / 150 mm	40 m / 30 m	0.82 kg
300 x 600 mm	5	200 mm	40 m	1.65 kg
450 x 450 mm	2 / 3	300 mm / 200 mm	60 m / 40 m	1.82 kg
450 x 900 mm	5	300 mm	60 m	3.62 kg

Other dimensions available on request

Colours

Default sign colour:	Yellow	Default character colour:	Black
Additional sign colours:	White Red Green Orange Blue	Additional character colours:	Yellow White Red Green Orange Blue

While choosing the colours, ensure that there is sufficient contrast between the sign and the characters.

Specifications

Sign

Base:	1 mm steel.
Treatment:	Sendzimir galvanized
Yellow signs:	Lacquered on both sides 5 mu, two-layer polyester primer 20 mu
Additional colours:	Standard galvanized plate. Colour foil on both sides 80 mu

Plastic protection edge

Material:	Plastic with steel clamps inside.
-----------	-----------------------------------

Digits

Material:	Black rubber magnet + 0.8 mm black foil
Other colours:	0.5 mm magnetic rubber + colour foil 80 mu.

Weight

Sign:	Approx. 8.0	kg/m ²
Protection edge:	Approx. 65	g/m
Digits:	Approx. 5	g/pc digit height 100
	Approx. 10	g/pc digit height 150
	Approx. 18	g/pc digit height 200

Approx. 40

g/pc digit height 300